

AmeriVap Systems - Product Comparison

AmeriVap Model:	5.5 KW	9 KW	10 KW	19.5 KW	20 KW	30 KW	33 KW	40 KW	50 KW	60 KW	80 KW
Product Line:	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial	Industrial
Power Consumption:	5.5 KW	9 KW	10 KW	19.5 KW	20 KW	30 KW	33 KW	40 KW	50 KW	60 KW	80 KW
AMPS:	** based on Volts	** based on Volts	** based on Volts	** based on Volts	** based on Volts	** based on Volts	40 amps	49 amps	61 amps	73 amps	91 amps
Steam Production:	18.5 lbs / hour	30 lbs / hour	30 lbs / hour	48 lbs / hour	55 lbs / hour	88 lbs / hour	88 lbs / hour	138 lbs / hour	173 lbs / hour	207 lbs / hour	258 lbs / hour
Water Tank Capacity:	1.25 gal	2.75 gal.	7 gal.	6.25 gal.	7 gal.	6.25 gal.	7 gal.	25 gal.	25 gal.	25 gal.	25 gal.
Detergent Tank Capacity:	1.25 gal	2.75 gal.	2.6 gal.	1.25 gal.	2.6 gal.	1.25 gal.	2.6 gal.	7 gal.	7 gal.	7 gal.	7 gal.
Boiler Capacity:	1.0 gal	1.0 gal	4.0 gal	4.5 gal	4.0 gal	4.0 gal	4.5 gal	8.2 gal	8.2 gal	8.2 gal	25 gal
Working Time:	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7	24 / 7
Working Pressure:	0 - 150 psi	0 - 150 psi	0 - 160 psi	0 - 150 psi	0 - 160 psi	0 - 150 psi	0 - 160 psi	0 - 180 psi	0 - 180 psi	0 - 180 psi	0 - 180 psi
Boiler Temperature:	365° F	365° F	370° F	365° F	370° F	365° F	370° F	380° F	380° F	380° F	380° F
Temperature at Tip:	220° F	220° F	220° F	220° F	220° F	220° F	220° F	220° F	220° F	220° F	220° F
Net Weight (Empty):	71 lbs	205 lbs	460 lbs	255 lbs	255 lbs	282 lbs	430 lbs	460 lbs	870 lbs	870 lbs	1005 lbs
Voltage:	208/220V or 480V 60HZ **	208/220V or 480V 60HZ **	208/220V or 480V 60HZ **	208/220V or 480V 60HZ **	208V, 480V or 575V 60HZ **	480V or 575V 60HZ **	480V - 60HZ	480V - 60HZ	480V - 60HZ	480V - 60HZ	480V - 60HZ
Phase:	3 Phase	3 Phase	3 phase	3 phase	3 phase	3 phase	3 phase	3 phase	3 phase	3 phase	3 phase
Machine Size:	14 x 26 x 39	21 x 26 x 39	43 x 23 x 37	34 x 20 x 37	43 x 23 x 37	43 x 23 x 37	34 x 20 x 37	72 x 30 x 42	72 x 30 x 42	72 x 30 x 42	72 x 30 x 42

Recommended for:

Houdini Jet System:	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes
Houdini Brush System:	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No

AmeriVap Model:	Steamax	VaporBlitz II	VaporBlitz I	3.3 KW
Product Line:	Commercial	Commercial	Commercial	Commercial
Power Consumption:	1700 W	1700 W	1700 W	3.3 KW
AMPS:	14.7 amps	14.7 amps	14.7 amps	15 amps
Steam Production:	8 lbs / hour	8 lbs / hour	8 lbs / hour	8.4 lbs / hour
Water Tank Capacity:	N/A	N/A	3.0 qt	1.25 gal
Detergent Tank Capacity:	N/A	N/A	N/A	1.25 gal
Boiler Capacity:	1.5 qt	2.64 qt	1.0 qt	1.5 qt
Working Time:	1.5 - 2 hours	1.5 - 2.5 hours	24 / 7	24 / 7
Working Pressure:	45 - 55 - 65 psi	45 - 55 - 65 psi	45 - 55 - 65 psi	0 - 105 psi
Boiler Temperature:	290° F	290° F	290° F	325° F
Temperature at Tip:	220° F	220° F	220° F	220° F
Net Weight (Empty):	14 lbs	15 lbs	19 lbs	66 lbs
Voltage:	115 V	115 V & 220 V	115 V & 220 V 60HZ	208/220V 60HZ
Phase:	Single Phase	Single Phase	Single Phase	Single Phase
Machine Size:	18 x 12 x 11	18 x 13 x 12	20 x 14 x 12	24 x 14 x 39

Recommended for:

Houdini Jet System:	No	No	No	No
Houdini Brush System:	No	No	No	No

** Power Package available: 208V, 220V, 240V, 380V, 440V, 480V, 575V

	5.5 KW	9 KW	19.5 KW	20 KW	30 KW
208 V	16 amps	25 amps	55 amps	57 amps	N/A
240 V	14 amps	22 amps	47 amps	N/A	N/A
380 V	9 amps	14 amps	30 amps	N/A	N/A
440 V	8 amps	12 amps	26 amps	N/A	N/A
480 V	7 amps	11 amps	24 amps	26 amps	38 amps
575 V	6 amps	10 amps	20 amps	24 amps	31 amps

AMERIVAP® SYSTEMS
Fresh thinking about clean™

www.amerivap.com

404-350-0239